



浙江野马电池有限公司
ZHEJIANG MUSTANG BATTERY CO.,LTD.



浙江野马电池有限公司
ZHEJIANG MUSTANG BATTERY CO.,LTD.

MATERIAL SAFETY DATA SHEETS

ALKALINE BATTERY

ZHE JIANG MUSTANG BATTERY CO., LTD

No.818 Rongji road, Luotuo, Zhenhai district, Ningbo, P.R.China

WEB: WWW.MUSTNAGBATTEY.COM

TEL:0086-574-86593245

FAX:0086-574-86593227





Material Safety Data Sheet

1. Product identification:

Chemical name: alkaline battery

Chemical system: Zn / MnO₂ / KOH

Applicable sizes: all alkaline batteries

2. Manufacturer:

ZHEJIANG MUSTANG BATTERY CO., LTD

Address: No.818 Rongji road, Luotuo, Zhenhai district, Ningbo, P.R.China

3. Hazardous ingredients/identity information

Chemical identity	Approximate value (%Wt)	OSHA PEL	ACGIH TLV	Appearance
Zinc (Zn)	/	NA	NA	Silvery solid
Manganese Dioxide (MnO ₂)	/	Note 2	Note 2	Black-brown powder
Potassium Hydroxide (KOH)	/	NA	NA	White solid
Carbon black	/	Note 3	Note 3	Black granule
Ion water	/	NA	NA	Liquid
Steel	/	NA	NA	Metal solid
Mercury	≤1ppm (note 1)	NA	NA	Atom state
Cadmium	≤250ppm (note 1)	NA	NA	Atom state
Lead	≤4000ppm (note 1)	NA	NA	Atom state

Note 1: the contents of heavy metal (mercury, cadmium and lead) confirms to the requirements of 98/101/EC.

Note 2: Manganese Dioxide (as Mn)—5mg/m³ (ceiling) (OSHA); 0.2mg/m³ (as Mn/ ACGIH)

Note 3: Carbon black—15mg/m³ (total dust, OSHA); 7.5mg/m³ (respirable fraction, OSHA); 2.0mg/m³ (ACGIH)

***These levels are not anticipated under normal consumer use conditions.

***ACGIH: American Council of Governmental Industrial Hygienists

***OSHA: Occupational Safety and Health Administration (U.S)

***PEL: Permissible Exposure Limit

***TLV: Threshold Limit Value

4. Physical Chemical Characteristics:



浙江野马电池有限公司
ZHEJIANG MUSTANG BATTERY CO., LTD.

Chemical identity	Specific gravity	Boiling point	Melting point	Odor	Corrosion	Toxicity	Flammability
Zinc (Zn)	7.09g/cm ³	907°C	419°C	None	None	None	None
Manganese Dioxide (MnO ₂)	5.026g/cm ³	535°C	390°C	None	None	None	None
Potassium Hydroxide (KOH)	2.04g/cm ³	1320°C	360.44°C	None	Slight corrosion	None	None
Carbon black	/	/	/	None	None	None	None
Ion water	1.0 g/cm ³	100°C	/	None	None	None	None
Steel	7.8 g/cm ³	2750°C	1535°C	None	None	None	None
Mercury	13.6g/cm ³	357°C	-39.3°C	None	None	Note 4	None
Cadmium	8.64g/cm ³	765°C	321.1°C	None	None	Note 4	None
Lead	11.34g/cm ³	1740°C	327.5°C	None	None	Note 4	None

Note 4: the contents of heavy metal (mercury, cadmium and lead) conforms to the requirements of 98/101/EC.

The following components are found in a "MUSTANG" battery with metal jacket.

Component	Material	Formula	CAS#
Positive electrode	Manganese dioxide	MnO ₂	1313-13-9
	Black carbon	C	7782-42-5
Negative electrode	Zinc	Zn	7440-66-6
Electrolyte	Potassium Hydroxide	KOH	1310-58-3
Metal-Jacket	Steel	Fe	/

5.Reactivity:

Stability	<input checked="" type="checkbox"/> stable	<input type="checkbox"/> unstable	Polymerization	<input type="checkbox"/> may occur	<input checked="" type="checkbox"/> will not occur
<u>Conditions to avoid</u> Do not heat, crush, and disassemble, short circuit or recharge.			<u>Conditions to avoid</u> Not applicable		
<u>Incompatible materials</u> Not applicable.			<u>Hazardous decomposition products</u> Thermal degradation may produce hazardous fumes of zinc and manganese; such as hydrogen gas.		

Warning signals: not applicable.

6.Physical data (for the battery)



浙江野马电池有限公司
ZHEJIANG MUSTANG BATTERY CO., LTD.

Boiling point: <u>NA</u> °F; <u>NA</u> °C	Melting point: <u>NA</u> °F; <u>NA</u> °C	Freezing point: <u>NA</u> °F; <u>NA</u> °C
Specific gravity (H ₂ O=1): <u>NA</u>	Vapor density (air=1): <u>NA</u>	Vapor pressure: <u>NA</u> mm Hg
Evaporation: <u>NA</u>	Saturation in air: <u>NA</u>	Autoignition temperature: <u>NA</u>
% Volatiles: <u>NA</u>	Solubility in water: <u>NA</u>	PH: <u>NA</u>
Appearance/Color: Cylindrical batteries. Contents dark in color.		
Flash point and test methods: NA		
Flammable limits in air (% by volume): lower <u>NA</u> %; upper <u>NA</u> %		
7.Routes/Effects of Exposure: These chemicals and metals are contained in a sealed can. For consumer use, adequate hazard warnings are included on both the package and on the battery. Potential for exposure should not exist unless the battery leaks, is exposed to high temperature or is mechanically, physically, or electrically abused. 1.Inhalation: Respiratory (and eye) irritation may occur if fumes are released due to heat or an abundance of leaking batteries. 2.Ingestion: Not anticipated due to size of batteries; choking may occur may with the small AAA battery. Irritation, including caustic burns/injury, may occur following exposure to a leaking battery. 3.Skin: <u>a. Contact:</u> Irritation, including caustic burns/injury, may occur following exposure to a leaking battery. <u>b. Absorption:</u> Not applicable. 4.Eye contact: Irritation, including caustic burns/injury, may occur following exposure to a leaking battery. 5.Other: Not applicable.		
8.Environmental impact 1.Dot hazard class: Not applicable. 2.Environmental effects: All "MUSTANG" carbon zinc batteries are manufactured with "no mercury added". These batteries are classified by the federal government as a non-hazardous waste and are safe for disposal in the normal municipal waste stream.		
9.Exposure control methods: 1.Engineering controls: General ventilation under normal use conditions. 2.Eye protection: None under normal use conditions. Wear safety glasses when handling leaking batteries. 3.Skin protection: None under normal use conditions. Use neoprene, rubber or latex-nitrile gloves when handling leaking batteries. 4.Respiratory protection: None under normal use conditions. 5.Other: Keep batteries away from small children.		
10.Work practices: <u>1.Handling and storage:</u> Store at room temperature. Avoid mechanical or electrical abuse. Do not short or install incorrectly. Batteries may explode or vent if disassembled, crushed. Recharged or exposed to high temperatures. Install batteries in accordance with equipment instructions. Do not mix battery systems, such alkaline and zinc carbon, in the same equipment. Replace all batteries equipment at the same time. Do not carry batteries loose in pocket or bag. <u>2.Normal clean up:</u> Not applicable. <u>3.Waste disposal methods:</u> Individual consumers may dispose of spent (used) batteries with household trash. Do not incinerate, since batteries may explode at excessive temperatures.		



浙江野马电池有限公司
ZHEJIANG MUSTANG BATTERY CO., LTD.

11. Emergency procedures:

1. Steps to be taken if materials is released to the environment or spilled in the work area:

Notify safety personnel of large spills. Slight caustic zinc chloride and Ammonium chloride may be released from leaking or ruptured batteries. Avoid eye or skin contact and inhalation of vapors. Increase ventilation. Clean-up personnel should wear appropriate protective gear.

2. Fire and explosion hazard:

In case of fire, carbon dioxide, carbon monoxide and other toxic organic substances will be generated. Do not inhale fumes and smoke.

3. Extinguishing media:

Carbon dioxide, foam, dry chemical power.

4. Extinguishing media not to be used:

Never use a direct water jet.

5. Firefighting Procedures:

Use self-contained breathing apparatus and full protective gear.

12. First aid and medical emergency procedures

1. Eyes:

Not anticipated. If battery is leaking and material contacts eyes,

First :flush eyes thoroughly with tepid water for 15 minutes.

Second: flush eyes with 3% H₃BO₃ (Boracic Acid)

Third: Contact physician at once.

2. Skin:

Not anticipated. If battery is leaking and material contacts eyes, flush with copious amounts of clear, tepid water for 15 minutes. If irritation, injury or pain persists, consult a physician.

3. Inhalation:

Not anticipated. Rinse the mouth and surrounding area with clear, tepid water for at least 15 minutes. Consult a physician immediately for treatment and to rule out involvement of the esophagus and other tissues.

4.

13. Toxicological information:

The product is multi component mixture for which no toxicological data exists.

14. Ecological information:

In general, no ecological data is available for preparations.

Precautions avoid disposing into drainage systems and in the environment.

15. Disposable considerations:

Do not dispose of into environment or into sewerage. If recycling is not possible, the product and its container have to be disposed of in accordance with your local legislation and regulations.

16. Transport information:

Road: not regulated

Air: not regulated

Sea: not regulated.

Remark: Batteries must be protected from short circuit and protected from movement that could lead to short circuit.

33021101036399